


3GDN



:CNEx21.1477X

| | | |
|-----|---------|-----------------|
| | 出 | |
| 齐平 | DC二 .NO | 3GDN-M12-DO2-EX |
| | DC二 .NC | 3GDN-M12-DC2-EX |
| 非齐平 | DC二 .NO | 3GDN-M12-DO4-EX |
| | DC二 .NC | 3GDN-M12-DC4-EX |

| | |
|-------------------------------|------------------|
| ABS | |
| : 2mm | : 4mm 10%± |
| / () | |
| : M2*52, | : M2*52 |
| | 12× 12× 1t |
| DC | |
| NO/NC | |
| 3.8mm 2 PUR | |
| 24 VDC | |
| 10-30 VDC | |
| : 800 Hz | : 500 Hz |
| -25 °C - +75 °C | |
| 200 nA | |
| <15% (Sr) | |
| IEC IP67 | |
| LED | |
| 10 55Hz | 1.5mm X Y Z 2h |
| 3% | |
| 6V | |
| 10mA | |
| Ex mb IIC T6 Gb/Ex mbD 21 T80 | |
| GB3836.1-2010 1 | GB3836.9-2014 9 |
| GB12476.1-2013 1 | GB12476.6-2010 6 |



| | | |
|----|----|----|
| BN | BU | BK |
|----|----|----|